

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ :

G03F 7/00, 1/14, 7/20

A1

(11) International Publication Number:

WO 98/12603

(43) International Publication Date:

26 March 1998 (26.03.98)

(21) International Application Number: PCT/IB97/01277

(22) International Filing Date: 22 September 1997 (22.09.97)

(30) Priority Data:

9619839.5

23 September 1996 (23.09.96)

GB

(71) Applicant (for all designated States except US): HUGLE LITHOGRAPHY INC. [US/US]; Suite 1500, 160 W. Santa Clara Street, San Jose, CA 95113 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VÖLKEL, Reinhard [DE/CH]; Rue Matile 8, CH-2000 Neuchâtel (CH). HERZIG, Hans-Peter [CH/CH]; Bel-Air 11, CH-2000 Neuchâtel (CH). BLATTNER, Peter [CH/CH]; Rue Matile 8, CH-2000 Neuchâtel (CH).

(74) Agent: GIBSON, Stewart, Harry; Urquhart-Dykes & Lord, Three Trinity Court, 21-27 Newport Road, Cardiff CF2 1AA (GB).


(81) Designated States: CN, JP, KR, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: PHOTOLITHOGRAPHY MASKING ARRANGEMENTS



(57) Abstract

A photomask arrangement comprises an array of optical elements (30) (e.g. microlenses) arranged to receive a uniform beam of light and to concentrate light onto respective points, lines or other areas of a photoresist layer (20). In this way, the light passing through each optical element is converged or concentrated onto a smaller area, thus maximising the use of the available light.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

PHOTOLITHOGRAPHY MASKING ARRANGEMENTS

The present invention relates to photolithography and more particularly to masking or imaging arrangements for imaging a pattern onto a photoresist coating.

There are a number of applications where it is required
5 to image an array of dots or other shapes onto a photoresist coating. One example is in the formation of arrays of field emitters for a field emission display type of flat panel display. Hitherto, a conventional photomask has been used, comprising a glass plate having a chromium coating which has
10 an array of apertures corresponding to the dot matrix to be formed on the photoresist coating on a separate substrate. Light is passed through the photomask and transferred onto the photoresist coating, but the major part of the light is blocked by the chromium coating, so that the process is relatively
15 inefficient.

We have devised improved photomask arrangements which are substantially more efficient.

In accordance with the present invention, there is provided a photomask arrangement which comprises an array of
20 optical elements and means for providing a uniform beam of light incident on said array, each optical element being arranged to concentrate light onto a respective point, line or other area of a photoresist layer.

The optical elements may take any of a variety of
25 forms, for example refractive or diffractive microlenses (e.g. spherical, cylindrical or elliptical in shape), diffraction gratings, apertures etc. Where the optical elements comprise lenses, each lens causes the light passing through it to converge onto an area of smaller size than the lens itself.
30 The lens array may be in direct contact with the photoresist layer, or it may be positioned at a small distance from the photoresist layer.

Each lens (or other optical element) may have a diameter generally in the range 2 to 500 microns, more
35 typically in the range 2 to 50 microns. Instead of being circular, the lenses or other optical elements may be of any

other desired shape (e.g. cylindrical, annular, square, rectangular, elliptical, etc.) and arranged to form an array of dots, lines, circles, squares, rectangles etc. on the photoresist coating.

5 The photomask arrangement may make use of the self-imaging effect (Talbot effect) to image the periodic mask pattern onto the photoresist, when the latter is positioned at the Talbot distance (or a multiple of the Talbot distance) behind the mask.

10 The photomask arrangement may make use of the fractional Talbot effect to image the mask pattern onto the photoresist, when the latter is positioned at a fraction of the Talbot distance behind the mask. In this case the photomask preferably comprises a binary phase mask.

15 An advantage of the arrangements which use the Talbot effect or the fractional Talbot effect is that in these cases the substrate with the photoresist is positioned at a significant distance from the photomask: in certain applications this is a necessary or desirable condition.

20 Embodiments of the present invention will now be described by way of examples only and with reference to the accompanying drawings, in which:

FIGURE 1 is a diagrammatic sectional view through a conventional photomask arrangement;

25 FIGURE 2 is a similar sectional view through a first embodiment of photomask arrangement in accordance with the present invention;

FIGURE 3 is a diagram to show the distribution of light waves behind each lens of the photomask shown in Figure 2;

30 FIGURE 4 is a sectional view similar to Figure 2, showing a second embodiment of photomask arrangement in accordance with the invention, which uses the self-imaging effect (Talbot effect); and

FIGURE 5 is a similar sectional view, showing a third
35 embodiment of photomask arrangement in accordance with the invention, which uses the fractional Talbot effect.

Referring to Figure 1, there is shown a conventional photomask arrangement, in which a uniform beam of UV light is passed through a photomask 10 onto a photoresist coating 20 on

a substrate 22. The photomask 10 comprises a glass plate 10 having a chromium coating 11 which is formed with a two-dimensional array of openings. It will be appreciated that only a small proportion of the UV light passes through the openings of the chromium coating 11 and onto the photoresist coating 20 of the substrate 22: the major proportion of the light is blocked by the chromium coating 11.

Figure 2 shows a photomask arrangement in accordance with the present invention, comprising a two-dimensional array of refractive plano-convex microlenses 30 (in this case carried on a support 31) mounted in contact with or closely spaced from the photoresist coating 20 of a substrate 22. A uniform beam of UV light is directed onto the array of microlenses. It will be appreciated that the photomask 30,31 accordingly forms a matrix of dots, with substantial compression relative to the size of the microlenses, at a distance f (the focal length of the lens) behind the mask.

Figure 3 shows the distribution of light waves behind a microlens of 5 microns diameter (and 2.5 microns lens height), which we have calculated by rigorous diffraction theory. This shows that the light is "funnelled" or concentrated into a small "pipe" of approximately 1 micron diameter and greater than 5 microns in length. Accordingly, a depth of focus of greater than 5 microns can be used for printing or imaging a dot approximately 1 micron in diameter.

The microlenses (or other optical elements) may be of any desired shape, e.g. circular, cylindrical, annular, square, rectangular, elliptical, etc., arranged to generate a two-dimensional array of dots, lines, circles, squares, rectangles etc. on the photoresist coating.

The photomask may be in direct contact with the photoresist coating, for example under vacuum conditions, so that the photomask (which is preferably flexible or conformable) follows any variations in the flatness of the substrate carrying the photoresist.

Instead, the photomask may be positioned at a short distance (up to 5 microns) from the photoresist coating: in this case, the photomask is rigid and therefore self-supporting.

Referring to Figure 4, the self-imaging effect (Talbot effect) may be used to image the matrix pattern onto the photoresist layer 20, when positioned at the correct distance behind the microlens array 30, i.e. in one of the succession of Talbot planes, spaced at successive distances ΔZ_T behind the focal plane, where

$$\Delta Z_T = \frac{\lambda}{1 - \sqrt{1 - \lambda^2/d^2}}$$

λ being the wavelength of light used and d being the fundamental period of the microlenses or other optical elements. Here again, the photomask array is rigid and self-supporting. Also, a compression ratio is achieved comparable to the arrangement of Figure 2.

Figure 5 shows use of the fractional Talbot effect, using a mask 40 in the form of a binary phase mask (having a matrix of transparent areas 42, e.g. square in shape). Light passed through this mask forms a Fresnel image of this pattern, with a pure amplitude modulation, at a distance of $0.5 Z_T$ behind the mask: by placing a substrate at this position, having a photoresist coating, the matrix of squares is printed in that photoresist coating. Again, a substantial compression ratio can be achieved.

A further advantage of the arrangements which use the Talbot effect or the fractional Talbot effect is that the substrate on which the required pattern is to be imaged is placed at a significant distance from the mask: this is a necessary or desirable condition for certain applications.

It will be appreciated that the beam of light which is incident on the array of optical elements is uniform, that is to say it is unmodulated and does not carry any information. The pattern which is formed on the photoresist layer is created entirely by the pattern of the optical elements in their array.

CLAIMS

- 1) A photomask arrangement which comprises an array of optical elements and means for providing a uniform beam of light incident on said array, each optical element being
5 arranged to concentrate light onto a respective point, line or other area of a photoresist layer.
- 2) A photomask arrangement as claimed in claim 1, in which said optical elements comprise refractive or diffractive microlenses.
- 10 3) A photomask arrangement as claimed in claim 1, in which said optical elements comprise diffraction gratings or apertures.
- 4) A photomask arrangement as claimed in any preceding claim, in which each optical element is 2 to 500 microns in
15 diameter or width.
- 5) A photomask arrangement as claimed in any preceding claim, in which said optical elements are in contact with said photoresist layer.
- 6) A photomask arrangement as claimed in any one of claims
20 1 to 4, in which said optical elements are spaced from said photoresist layer.
- 7) A photomask arrangement as claimed in one of claims 1 to 4, in which the photoresist layer is spaced from the optical elements to make use of the self-imaging (Talbot) effect.
- 25 8) A photomask arrangement as claimed in any one of claims 1 to 4, in which the photoresist layer is spaced from the optical elements to make use of the fractional Talbot effect.
- 9) A photolithographic method, in which a uniform beam of light is directed onto an array of optical elements, each said

optical element being arranged to concentrate light onto a
respective point, line or other area of a photoresist layer.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB 97/01277

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G03F7/00 G03F1/14 G03F7/20

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G03F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 017, no. 669 (P-1657), 9 December 1993 & JP 05 224396 A (KURARAY CO LTD), 3 September 1993, see abstract	1-5, 9
X	PATENT ABSTRACTS OF JAPAN vol. 007, no. 030 (P-173), 5 February 1983 & JP 57 181549 A (MASATAKE SATOU), 9 November 1982, see abstract	1-5, 9
X	US 5 148 322 A (AOYAMA SHIGERU ET AL) 15 September 1992 see figures 19, 20, 23-26	1-7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

" Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

10 February 1998

Date of mailing of the international search report

27/02/1998

Name and mailing address of the ISA

European Patent Office, P. B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Haenisch, U

INTERNATIONAL SEARCH REPORT

Inter. Application No
PCT/IB 97/01277

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 368 482 A (SECRETARY TRADE IND BRIT) 16 May 1990 see the whole document ----	1-4,6,9
X	EP 0 486 316 A (NIPPON KOGAKU KK) 20 May 1992 see page 5, line 8 - line 24; figure 1 ----	1,3,4,6, 9
X	EP 0 707 237 A (COMMISSARIAT ENERGIE ATOMIQUE) 17 April 1996 see the whole document ----	1,2,4,5, 9
P,X	EP 0 759 578 A (COMMISSARIAT ENERGIE ATOMIQUE) 26 February 1997 see the whole document -----	1,2,4,5, 9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 97/01277

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5148322 A	15-09-92	US 5345336 A	06-09-94
EP 0368482 A	16-05-90	GB 2223861 A	18-04-90
		JP 3073954 A	28-03-91
EP 0486316 A	20-05-92	JP 4180612 A	26-06-92
		JP 4180613 A	26-06-92
		JP 4225357 A	14-08-92
		JP 4225358 A	14-08-92
		JP 4225359 A	14-08-92
		JP 4225514 A	14-08-92
EP 0707237 A	17-04-96	FR 2725558 A	12-04-96
		JP 8212910 A	20-08-96
		US 5669800 A	23-09-97
EP 0759578 A	26-02-97	FR 2737928 A	21-02-97
		JP 9153329 A	10-06-97
		US 5700627 A	23-12-97

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)